

Material safety data sheet for lead acid industrial batteries AGM / Gel

(Batterien wet, non spillable)

Battery series:

PzV Traction Bull und Traction Bull EEX PzVB Traction Bull und Traction Bull EEX OPzV Stand by Bull SBV Stand by Bull SBX Stand by Bull SBG Stand by Bull FAV Stand by Bull FPL Stand by Bull SCV Stand by Bull GiV (S) Stand by Bull GiVC Stand by Bull DB Traction Bull Bloc AGM Traction Bull Bloc

Transport information:

valid transport information from paragraph 14.2



ZVEI information leaflet No. 1e Edition October 2018

Instructions for the safe handling of lead-acid accumulators (lead-acid batteries)

The REACH-regulation (1907

/2006/EC) describes the setting up and updating of safety data sheets for substances and mixtures. For articles – like leadacid batteries – safety data sheets are **not** required.

The transfer of a leaflet with "instructions for the safe handling of batteries" has to be interpreted simply as a product information. The following of the format of a REACH safety data sheet with the respective information is useful from a product- and working safety's view but should not be confused with the (legal) requirements of a REACH safety data sheet.

This leaflet addresses users of batteries and is meant to apply voluntarily.

The notes are meant to help to comply with legal requirements but do not replace them.

1. Identification of the substance/mixture and of the company/undertaking

Data on the product

Trade name

Lead-acid battery filled with diluted sulphuric acid

Data on the manufacturer:

Telephone, Facsimile, etc.

2. Hazards identification

No hazards in case of an intact battery and observation of the instructions for use.

Lead-acid batteries have significant characteristics:

They contain diluted sulphuric acid, which may cause severe acid burns.


- During the charging process they develop hydrogen gas and oxygen, which under certain circumstances may turn into an explosive mixture.
- They have an internal voltage, which – depending on their level – can be dangerous to the human body when touched.

Standard EN 50272-2 includes safety requirements for batteries and battery installations and describes the basic precautions to protect against dangers deriving from electric currents, leaking gases or electrolytes.

3. Composition/information on ingredients

CAS-No	Description	Content	H-phrases
7439-92-1	blue lead, lead alloys with traces of As, Sb	32 Weight %	H360,H362 H332, H302, H372, H351
	lead-containing Battery paste	32 Weight %	H360D H302, H332, H361f, H412
7664-93-9	sulphuric acid	29 Weight %	H290, H314
	plastic case	7 Weight %	
Note: lead-material is a substance of REACH Candidate list.			

This leaflet was prepared by the Working Group on Environment and Occupational Health of the ZVEI - German Electrical and Electronic Manufacturer's Association, Batteries Division



General information:

Sulphuric acid	acts corrosive and damages tissue
after contact with skin	rinse with water, remove and wash wetted clothing
after inhalation of acid mist ²⁾	inhale fresh air
after contact with the eyes ²⁾	rinse under running water for several minutes
after swallowing ²⁾	drink a lot of water immediately, and swallow activated carbon
Lead-containing battery paste	classified as toxic for reproduction
after contact with skin	clean with water and soap

7. Handling and storage

measures

Store frost-free under roof: prevent short circuits.

Protect plastic housings against exposition to direct sun radiation.

Seek agreement with local water authorities in case of larger quantities.

If batteries have to be stored in storage rooms, it is imperative that the instructions for use are observed because gases can be formed during battery loading.

²⁾ Seek the advice of a doctor.

5. Firefighting measures

Suitable extinguishing agents

When electrical devices are set on fire in general water and foam are suitable extinguishing agents. For incipient fires CO₂ is the most effective agent. Fire brigades are trained to keep a distance of 1 m when extinguishing an electrical fire (up to 1 kV) with spray jet and a distance of 5 m with full jet. For electrical fires in electrical installations with voltages > 1 kV other distances are applicable depending on the respective voltage. For fires in photovoltaic installations other rules apply.

Unsuitable extinguishing agents

Powder fire extinguishers are not suitable, amongst others because of only minor efficiency, possible risks or collateral damages.

Special protective equipment

For larger stationary battery installations or larger stored quantities: protective goggles, respiratory and acid protective equipment, acid-proof clothing.

8. Exposure controls/ personal protection

8.1 No exposure caused by lead and lead-containing battery paste.

8.2 Possible exposure caused by sulphuric acid and acid mist during filling and charging.

Substance CAS-Nr.	sulphuric acid 7664-93-9	
H-phrases H290 H314	May be corrosive to metals. Causes severe skin burns and eye damage.	
P-phrases P280	Wear protective gloves/protective clothing/eye protection/face protection.	
P301+ P330 + P331 P303 + P361 + P353	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.	
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing.	
Threshold value on workplace: 0,1 mg/m ³		
Hazard symbol	P. Contraction of the second s	
	corrosive	
Personal protective equipment	Rubber-, PVC-gloves, acid-proof goggles, acid-proof clothing, safety boots	

9. Physical and chemical properties

Lead

Appearance: form: solid colour: grey odour: odourless

Safety-related data Solidification point: 327 °C Boiling point: 1740 °C Solubility in water (25 °C): Iow (0,15 mg/l)

density (20°C): 11,35 g/cm3

Sulphuric acid (30 - 38,5 %)

Appearance: form: liquid colour: colourless odour: odourless

Safety-related data Solidification point: - 35 to - 60°C

Boiling point: ca. 108 – 114 °C Solubility in water (25 °C): complete density (20 °C): 1,2 – 1,3 g/cm³

10. Stability and reactivity of sulphuric acid (30 to 38,5%)

Corrosive, inflammable liquid.

Thermal decomposition at 338 °C.

Destroys organic materials such as cardboard, wood, textiles.

Reacts with metals producing hydrogen.

Vigorous reactions with lyes and alkalis.

11. Toxicological information

Sulphuric acid Acts intensely corrosive on skin

and mucous membranes. The inhalations of mists may cause damage to the respiratory tract.

Lead and leadcontaining battery paste

May cause damage to the blood, nerves, and kidneys when taken in. Lead-containing battery paste is classified as toxic for

reproduction.

12. Ecological information

Preliminary remark: Relevant only if release of sulphuric acid is caused by destruction of the battery.

Sulphuric acid

Water-polluting liquid within the meaning of the German Water-Resources Act (WHG) Water pollution class: 1 (mildly water polluting).

As described in section 6 use a bonding agent, such as sand, to absorb spilled acid or neutralise using lime / sodium carbonate. Dispose of under the locally applicable provisions.

Dispose with due regard to official local regulations.

Do not allow progression into the sewage system, soil or bodies of water.

Lead and leadcontaining battery paste

Are hardly soluble in water.

Lead can be dissolved in an acidic or alkaline environment. Chemical and physical treatment is required for elimination from water. Waste water containing lead must not be disposed of in untreated condition.

13. Disposal considerations

The points of sale, the manufacturers and importers of batteries, respectively the metal dealers take back spent batteries, and render them to the secondary lead smelters for processing.

Spent lead-acid batteries are not subject to accountability of the German Waste Prove Ordinance. They are marked

with the recycling / return symbol and with a crossed-out roller container (cf. chapter 15 "Regulatory information").

Spent lead-acid batteries are not allowed to dispose in the domestic waste or be mixed with other batteries in order not to compliance the processing and to prevent danger to humans

and the environment.

By no means may the electrolyte, the diluted sulphuric acid, be emptied in an inexpert manner. This process is to be carried out by the processing companies.

14. Transport information

14.1 Batteries, wet, filled with acid

Land transportation according to ADR/RID

- Special Provision 598: no transport as dangerous goods (new + spent batteries are not subject to other requirements of ADR/RID if they meet the requirements according to Special Provision 598):
 - a. New storage batteries when:
- they are secured in such a way that they cannot slip, fall or be damaged;
- they are provided with carrying devices, unless they are suitably stacked, e.g. on pallets;
- there are no dangerous traces of alkalis or acids on the outside;
- they are protected against short circuits;
- b. Used¹ batteries when:
- their cases are undamaged;
- they are secured in such a way that they cannot leak, slip, fall or be damaged, e.g. by stacking on pallets;
- there are no dangerous traces of alkalis or acids on the outside of the articles;
- they are protected against short circuits;

If the requirements of Special Provision 598 are not fulfilled the transport of new and spent batteries has **to be declared as dangerous goods** as follows:

- UN-no.: 2794
- Naming and description: BATTERIES, WET, FILLED WITH ACID
- Hazard class: 8
- Packing group: none
- Hazard label: 8
- ADR Tunnel restriction code: E

Sea transportation

- according to IMDG Code
- UN-no.: 2794
- Proper shipping name: BATTERIES, WET, FILLED WITH ACID

- Hazard class: 8
- Packaging group: none
- Packaging Instruction: P 801
- EmS: F-A, S-B
- Hazard label: 8

Air transportation according to IATA-DGR

- UN-no.: 2794
- Proper shipping name: BATTERIES, WET, FILLED WITH ACID
- Class: 8
- Packaging group: none
- Packaging Instruction: 870
- Hazard class: (8) Corrosive

14.2 Batteries,

wet, nonspillable

Land transportation according to ADR/RID

- UN-no.: 2800
- Proper shipping name: BATTERIES, WET, NON-SPILLABLE
- Hazard class: 8
- Packing group: none
- Packaging Instruction: P 003, P 801a
- Hazard label: 8
- Special Provision 238 para. a) + b): **no transport as dangerous goods** (nonspillable batteries are not subject to other requirements of ADR/RID if they meet the requirements according to special provision 238. **An appropriate**

manufacturer`s confirmation is necessary.

Batteries which do not meet the requirements according to Special Provision 238 have to be packed and carried as listed in 14.1 Land transportation ADR/RID according to Special Provision 598).

Sea transportation according to IMDG Code

- UN-no.: 2800
- Proper shipping name: BATTERIES, WET, NON-SPILLABLE
- Hazard class: 8
- Packing group: none
- Packaging Instructions:
 P 003 and PP 16
- EmS: F-A, S-B

¹ "Used storage batteries" means storage batteries carried for recycling at the end of their normal service life.

Special Provision 238 no. 1 + 2: **no transport as dangerous goods** (nonspillable batteries are not subject to other requirements of IMDG Code if they meet the requirements according to Special Provision 238. **An appropriate manufacturer's confirmation is necessary.** Batteries which do not meet

Batteries which do not meet the requirements according to Special Provision 238 have to be packed as listed in 14.1 Sea transportation IMDG Code according to Packaging Instruction P 801 and carried as dangerous goods according to UN 2794).

Air transportation according to IATA DGR

UN-no.: 2800

- Proper shipping name: BATTERIES, WET, NON-SPILLABLE
- Hazard class: 8
- Packing group: none
- Packaging Instruction: 872
- Hazard label: (8) Corrosive
- Special Provision A 67: no transport as dangerous goods (non-spillable batteries are not subject to other requirements of IATA DGR if they meet the requirements of Special Provision A 67. Provided that poles are secured against short-circuit. An appropriate manufacturer's confirmation is necessary. Batteries which do not meet

the requirements according to Special Provision A 67 have to be packed as listed in 14.1 Air transportation IATA-DGR according to Packing Instruction 870 and carried as dangerous goods according to UN 2794).

14.3 Batteries, damaged:

Land transportation according to ADR/RID

- UN-no.: 2794
- Proper shipping name: WASTE, BATTERIES, WET, FILLED WITH ACID, ENVIRONMENTALLY HAZARDOUS²
- Hazard class: 8
- Packing group: none

Transport as dangerous goods considering:

- Packing Instruction P 801 a: packing in accu boxes
 Or
- (ii) Special Provisions VC1, VC2, AP8: in bulk
- Hazard label: 8
- ADR Tunnel restriction code: E

Note: these references can be applied by transportation of Lead-acid batteries of UN-no. 2800 as well.

15. Regulatory information

All types of batteries and accumulators, regardless of their shape, volume, weight, material composition or use are governed by the European battery

directive (2006/66/EG). It contains rules regarding the placing on the market, collection, treatment, recycling and disposal of waste batteries and accumulators. Furthermore all lead-acid batteries have to be marked with a crossed-out wheelie bin and with the chemical symbol for lead Pb shown below.



In addition, the ISO- recycling symbol is marked.



The manufacturer, respectively the importer of the batteries shall be responsible for the attachment of the symbols. In addition, a consumer / user information on the significance

of the symbols has to be attached. The manufactures and sellers of the batteries subject to identification requirements (packaging, technical instructions, leaflets) shall be responsible for this information.

16. Other information

The data rendered above are based on today's knowledge, and do not constitute an assurance on properties.

Existing laws and regulations have to be observed by the recipient of the product in own responsibility.



Die Elektroindustrie

Editor:

ZVEI - German Electrical and Electronic Manufacturers' Association Batteries Division

Lyoner Straße 9 60528 Frankfurt

Phone: +49 69 6302-283

Fax: +49 69 6302-362 Mail: batterien@zvei.org

© ZVEI 2016

In spite of all due care, however, we cannot accept any liability that the information is complete or correct or up to date.

² The note «ENVIRONMENTALLY HAZARDOUS» has to be attached when transporting in bulk.

BULGARIEN

Banner Baterii Bulgaria EOOD / Баннер Батерии Б-я ЕООД Ul. Ljublana 46, J&L Center, 1. Stock / Ул. Любляна 46, J&L Center, ет. 1., BG-1618 Sofia / София Telefon: / Тел. +359/2/889 01 20 Fax: / Факс: +359/2/889 01 21 E-Mail: office.bbg@bannerbatteries.com

DÄNEMARK

Banner Batterier Danmark ApS Silovej 14, DK-2690 Karlslunde Telefon: +45/70 20 60 61 Fax: +45/70 20 60 69 E-Mail: office.bdk@bannerbatteries.com

DEUTSCHLAND

Banner Batterien Deutschland GmbH Kesselbodenstraße 3, D-85391 Allershausen (München) Telefon: +49/(0)6441/30 73-23000 Fax: +49/(0)6441/30 73-23099 E-Mail: office.bda@bannerbatterien.com

Banner Batterien Deutschland GmbH -

Verkaufsniederlassung Lise-Meitner-Str. 5, D-41515 Grevenbroich (Düsseldorf) Telefon: +49/(0)6441/30 73-23500 Fax: +49/(0)6441/30 73-23599 E-Mail: office.bdg@bannerbatterien.com

Banner Batterien Deutschland GmbH -

Verkaufsniederlassung Am Schwingbach 14-16 D-35625 Hüttenberg/Rechtenbach (Frankfurt) Fax: +49/(0)6441/30 73-23199

Banner Batterien Deutschland GmbH -

Verkaufsniederlassung Mutzschen E-Mail: office.bdm@b

Banner Batterien Deutschland GmbH -

Verkaufsniederlassung Pforzheim Südweg 6, D-75245 Neulingen-Göbrichen (Pforzheim) -E-Mail: office.bdp@ban

Banner Batterien Deutschland GmbH -Verkaufsniederlassung

Friedrich-Bückling-Str. 21, D-16816 Neuruppin (Berlin) Fax: +49/(0)6441/30 73-23499 E-Mail: office.bdne@bannerbatterien.com

FRANKREICH

Banner France SAS Zone Industrielle No. 2, 5, Rue Vauban, F-68170 Rixheim Fax: +33/(0)389/54 13 28 E-Mail: office.bf@bannerbatteries.com

Banner Toulouse - Succursale Telefon: 05/61 32 72 11 Fax: 05/61 32 88 94

Banner Ile de France - Succursale

Parc GVIO - Hall 1 - Batiment D , 86/114, avenue Louis Roche, F-92230 Gennevilliers Telefon: 01/47 94 32 75 Fax: 01/47 98 05 19 E-Mail: office.bfp@bannerbatteries.com

GROSSBRITANNIEN

Banner Batteries (GB) Ltd. Units 5-8 Canal View Business Park, Wheelhouse Road, Rugeley, UK-WS15 1UY Staffordshire Telefon: +44/(0)1889/57 11 00 Fax: +44/(0)1889/57 73 42 E-Mail: office.bgb@bannerbatteries.com

ÖSTERREICH

Banner GmbH Fax: +43/(0)732/38 88-21399 E-Mail: office@bannerbatterien.com

Banner Batterien Österreich GmbH Banner Straße 1, A-4021 Linz

E-Mail: office@bannerbatterien.com

Banner/EAST PENN Battery Services GmbH Banner Straße 1, A-4021 Linz

Banner Straße 1, A-4021 Enter Telefon: +43/(0)732/38 88-0 Fax: +43/(0)732/38 88-21399 F Mally office@banner batterien.com

Banner Kunststoffwerk GmbH Traunauweg 22, A-4030 Linz Telefon: +43/(0)732/38 88-21800 Fax: +43/(0)732/38 88-21850 E-Mail: office@bannerkunststoff.com

Banner Batterien Österreich GmbH -

Verkaufsniederlassung Kärntner Str. 168, A-8053 Graz Telefon: 0316/27 21 52-22100 Fax: 0316/27 21 52-22199 E-Mail: office.bag@bannerbatterien.com

Banner Batterien Österreich GmbH -

Verkaufsniederlassung Bundesstr. 4, A-6063 Innsbruck/Rum Telefon: +43/(0)512/26 20 70-22200 E-Mail: office.bai@bannerbatterien.com

Banner Batterien Österreich GmbH -Verkaufsniederlassung Banner Str. 1, A-4021 Linz

Fax: +43/(0)732/38 88-21699 E-Mail: office.bal@ban

Banner Batterien Österreich GmbH -Verkaufsniederlassung Lehenweg 6, A-6830 Rankweil Fax: +43/(0)5522/45 3 57

Banner Batterien Österreich GmbH -Verkaufsniederlassung Lamezanstr. 5, A-1232 Wier Telefon: 01/616 51 81-22000 Fax: 01/616 21 90

E-Mail: office.baw@bannerbatterien.com Banner Batterien Österreich GmbH -

Verkaufsniederlassung Steingasse 207, A-9020 Klagenfurt Telefon: 0463/33 7 22-22400

POLEN

Banner Polska Sp. z o.o. ul. Gliwicka 234, PL-40861 Katowice Telefon: +48/(0)32/203 72 45 Fax: +48/(0)32/203 72 46 E-Mail: office.bpl@bannerbatteries.com

Banner Polska Sp. z o.o. - Filia

ul. Kręta 2, PL-05850 Ozarów Mazowiecki (Warszawa) Telefon: +48/(0)22/721 14 47 Fax: +48/(0)22/721 14 48 E-Mail: office.bplw@bannerbatteries.com

RUMÄNIEN

Banner Baterii Romania s.r.l. B-dul Biruinței nr. 67, RO-077145 Pantelimon, jud. Ilfov Telefon: +4/021/3000 627, +4/021/310 11 49 batteries.com

RUSSLAND

OOO "Banner Batterien" / ООО «Баннер Баттериен» Krasnogorskij rajon, Promzona-37, pos.Archangelskoe /

RUS-143420 Moskovskaja Oblast / Московская область Telefon: / Телефон: +7/(499)504 9<u>8 69</u> Fax: / Факс: +7/(499)504 98 69

SCHWEIZ

Banner Batterien Schweiz AG / Batteries Banner Suisse SA Banner Straße 1, CH-5746 Walterswil Telefon: +41/(0)840 Banner (226637) Gratisfax: +41/(0)800 Banner (226637)

Banner Batterien Schweiz AG - Verkaufsniederlassung

Telefon: 0840 Banner (226637) Fax: 0800 Banner (226637) rbatterien.com E-Mail: office.bchw@bann

SLOWAKEI

Banner Baterie SR, s.r.o. Za Stanicou 1, Nr. 1537, SK-83104 Bratislava 3 Telefon: +421/(0)2/43 63 43 44 E-Mail: office.bskb@bannerbatteries.com

TSCHECHIEN

Banner Baterie ČR, s.r.o. Uhříněves, Přátelství 1011, CZ-10400 Praha 10 Telefon: +420/267 090-510 Fax: +420/267 090-522 E-Mail: office.bczp@bannerbatteries.com

TÜRKEI

Banner Akü San. ve Tic. Ltd. Şti. Beylikdüzü Mermerciler Sanayi Sit., 7. Cad. No:4 (Hellmann Logistik binası), TR-34520 Beylikdüzü - İstanbul Telefon: +90/212/877 85 10 Fax: +90/212/879 29 72 E-Mail: office.btri@bannerbatteries.com

UNGARN

Banner Batterien Hungária Kft Ipari park, Jedlik Ányos u. 6, H-2330 Dunaharaszti Telefon: +36/24/49 18 91 Fax: +36/24/49 18 92 E-Mail: office.bhb@bannerbatteries.com



Banner GmbH Banner Straße 1, A-4021 Linz 王朝₁₁434(Q)732/3888-0, Fax ++43/(0)732/3888-21399 bannerbatterien.com